



EASYCOAT

CAT EMULSI DALAMAN | INTERIOR EMULSION PAINT



Cheers* 6582



Butter Cream 6579



Lime Fizz 6003



Purple Angle 6015



Mango Gold* 6268



Mint Cool 6218




Cool Lime 6572



Precious Pink 6127




Pretty Lady 6088



Tracey Blue 6316



Golden Sage **New** BGG 1709D



Paloma* 6520



Rondo Yellow **New** 5534



Moody Blue 6166



Balinese Green **New** 5170



Blushing Pink **New** 5622




Butter Cup **New** 5873



Blue Mountain **New** 5639



Oyster Grey **New** 5874



Harrison Gray **New** N 1912T

-Semua warna yang ditunjukkan adalah hampir serupa dengan warna sebenar Nippon Paint berdasarkan teknik percetakan moden.
All colours shown are as close to the actual Nippon Paint colour as modern printing techniques permit.

-Juga didapati dalam warna White 98 | Also available in White 98.

*Warna-warna Premium / *Premium colours





Note:

Colours representations on website may vary from actual paint colours. Visit your nearest Nippon Paint Colour Creations outlet(s) to get a physical colour card to confirm your colour choices.

Easycoat ialah cat emulsi dalaman berkualiti ekonomi, yang dirumus khas untuk hiasan dan lindungan permukaan seperti dinding batu, siling, plaster dan papan gentian. Cat ini dapat memberikan kemas yang memuaskan dengan harga yang sangat berpatutan.

Easycoat is an economy grade interior emulsion paint, that is specially formulated to enhance and protect surfaces such as masonry wall, ceiling, plastering substrate and fibre board. Easycoat gives a satisfying finishing with a very affordable price.



CADANGAN SISTEM SALUTAN Recommended Coating System

CAT ASAS Sealer	5200 Wall Sealer / 5400 Wall Sealer / Acrylic 5170 Wall Sealer / Hi-Bond Wall Sealer	1 Lapisan 1 Coat
CAT Topcoat	Easycoat	2 Lapisan 2 Coats



DATA PENGGUNAAN Application Data

TEMPOH KERING / *Drying Time:*

Kering Disentuh / *Touch Dry:*
20 minit / *minutes*

Kering Sempurna / *Hard Dry:*
1 jam / *hour*

Tempoh Lapisan Semula / *Recoating Time:*
2 jam / *hours*

(Bergantung pada suhu dan kelembapan /
Dependent on temperature and humidity)

Liputan Teori / *Theoretical Coverage:*
8 - 10 m² seliter / *per liter*

(Bergantung pada keadaan asas /
Dependent on substrate condition)

Cara Penggunaan / *Application Method:*

Cairkan dengan maksimum 10% air
bagi lapisan pertama dan kedua

*Dilute the paint with 10% of water
for 1st and 2nd coat*



PENYEDIAAN PERMUKAAN Surface Preparation

Tanggalkan semua cat yang mengelupas atau baki berserbuk. Baiki keretakan dan permukaan yang tidak rata dengan Multi-Purpose Joint Compound atau likatan yang sesuai. Ratakan kawasan likatan (putty/filler) dengan kertas pasir. Pastikan permukaan yang hendak dicat benar-benar bersih dan kering serta bebas daripada kotoran, minyak dan sebarang bahan-bahan pencemaran lain. Biarkan permukaan benar-benar bersih dan kering sebelum kerja mengecat dimulakan. Jangan mengecat jika kadar kelembapan dan kealkalian permukaan dinding masih tinggi.

Remove all loose, defective paint or powdery residues, loose chalk, dust and foreign matter. Repair cracks, uneven surfaces with Multi-Purpose Joint Compound or suitable fillers. Smoothen the putty/filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high.



**THE
COATINGS
EXPERT®**

NIPPON PAINT (M) SDN. BHD. (196701000578)

Lot I-17, Taman Perindustrian Subang Utama, Jalan SU 4,
40300 Shah Alam, Selangor Darul Ehsan, Malaysia.

☎ 1-800-88-2663 ✉ customer@nipponpaint.com.my

🏠 www.nipponpaint.com.my 📘 facebook.com/nipponpaintmalaysia