

9000 ALUMINIUM WOOD PRIMER
Updated Aug'16


9000 Aluminium Wood Primer is specially formulated for priming wooden surfaces. By virtue of its aluminium pigment being in flake-form, this paint forms an excellent sealer which prevents moisture penetration and at the same time levels the wood surfaces.

Product Features:

- Protection from moisture
- Good levelling

Paint Type	Product Type	Finishing	Recommended Substrate	Pack Size
Solvent based	Interior & Exterior	Metallic Aluminium Lustre	Wood	5 Litres

Composition

Pigment	: Aluminium
Binder	: Modified alkyd / Modified phenolic resin
Thinner	: Hydrocarbon

Technical Data

Drying Time	: Touch Dry : 30 minutes (Dependent on temperature and humidity)
	: Hard Dry : 8 hours (Dependent on temperature and humidity)
Recoating Time	: 8 hours (Dependent on temperature and humidity)
Dry Film Thickness	: Around 25 - 30 µm per coat (based on substrate condition)
No. of Coats	: 1 coat
Theoretical Coverage	: 12 - 15 m ² per litre per coat (Actual coverage is dependent on substrate condition, application method, application condition and finishing appearance)
Volume Solid	: ~ 60%
Shelf Life	: Up to 36 months in tight sealed container

Application Method

Brush / Roller	: The paint is ready for use after thorough stirring. If necessary, thin down with 5% of General Purpose Thinner.
	Brushing is the only recommended method. Applying a slight pressure on the brush when painting will help the bristles to work the paint into the wood grains and crevices to ensure best performance of the paint film.

Recommended Coating System

Sealer / Primer	: 9000 Aluminium Wood Primer	: 1 coat
Undercoat	: 9000 Undercoat / Economy Undercoat	: 1 coat
Top Coat	: 9000 Gloss Finish / Q-LAC Gloss Finish	: 2 coats

Surface Preparation

Surface must be dry and free from dirt, grease and other contaminants. Smoothen surface with sandpaper and then clean off and dry. The scraped areas should be spot-primed using an undercoat.

Cleaning

Clean up equipment with thinner immediately after use.

Safety Precautions

- Keep container tightly closed and keep out of reach children or away from food and drink.
- Ensure good Ventilation during application and drying.
- When applying paint, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- Paint must always be stored in a cool place.
- When transporting paint, care must be taken. Always keep container in a secure upright position.
- Dispose any paint waste in accordance with the appropriate Environment Quality Regulations.

- Keep container tightly closed and keep out of reach children or away from food and drink.
- Ensure good Ventilation during application and drying.
- When applying paint, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- Paint must always be stored in a cool place.
- When transporting paint, care must be taken. Always keep container in a secure upright position.
- Dispose any paint waste in accordance with the appropriate Environment Quality Regulations.

Note

* Theoretical Coverage is based on a mathematical formula

$$\left[\frac{\text{Volume Solid \%} \times 10}{\text{Dry Film Thickness}} \right] = \text{m}^2/\text{lit}/\text{coat}$$

and does not consider LOSS FACTORS.

Variables like porosity of substrate, application method, dilution ratio, dry film thickness, opacity and so on will affect the loss factor and can vary from 30% - 50% or even more.

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.