



**NIPPON
PAINT**

ECO-BOND

Anti-Peeling Sealer

- ✓ **Anti-peeling**
- ✓ **Ultra low odour**
- ✓ **Direct application on skim-coated and plastered wall**

NEW LOOK



Old Look



Eco-Bond Wall Sealer is a water-based anti-peeling sealer specially designed to be applied on skim-coated and plastered surfaces which is powdery in nature. It enhances the inter-coat bonding and promotes longevity to your top finishing coat.



Direction for use

1 Shake well before use.

2 Pour Eco-Bond Wall Sealer into a pail.



3 Dilute with water. (1:1 ratio)



4 Stir the mixture.



5 Apply with roller or spray.



6 Leave to dry completely before applying topcoat.

Application Data

Drying Time:

Touch Dry: 15 minutes

Hard Dry: 1 hour

Recoating Time: 2 hours

(Dependent on temperature and humidity)

Theoretical Coverage:

9 – 11 m² per liter

(Dependent on substrate condition)

Surface Preparation

Remove all loose, defective paint or powdery residues, loose chalk, dust and foreign matter. Repair cracks, uneven surfaces with Multi-Purpose Joint Compound or suitable fillers. Smoothen the putty/filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high.



**NIPPON
PAINT**

NIPPON PAINT (M) SDN. BHD. (196701000578)

Lot I-17, Taman Perindustrian Subang Utama, Jalan SU 4,
40300 Shah Alam, Selangor Darul Ehsan, Malaysia.

☎ 1-800-88-2663 ✉ customer@nipponpaint.com.my

🏠 www.nipponpaint.com.my 📘 facebook.com/nipponpaintmalaysia