



MATEX PRO

CAT EMULSI DALAMAN · INTERIOR EMULSION PAINT



Untuk Kegunaan Projek Sahaja
Project Use Only

MATEX PRO



Lebih Liputan
Better Coverage




Fungsi Anti-kulat
Anti-fungus Properties




Dirumus khas untuk kegunaan dinding dalaman. Ia memberi sapuan yang menarik, halus serta tahan lasak pada permukaan dinding, asbestos dan papan lembut serta papan keras. Matex Pro boleh meliputi kawasan yang luas dan mudah disapu.


Specially formulated emulsion paint for interior wall. It provides a durable and attractive smooth finish on walls, asbestos, hard boards and soft boards. Matex Pro has better coverage and is easy to apply.




White **BS 9102**




Cool White **563**




Sunrise Blue **454**




Morning Dew **3202**



Dove **592**




Gray Whisper **PRO 0031**




Velvet Touch **OW 1051P**



Moonshadow **177**




Crystal White **591**




Gray Dew **OW 1086P**



Antique White **369**



Orchid White **472**




Vanity **9207**




Latte **604**



Rustic Charm **PRO 0035**



Blonde White **588**



Merry White **589**



Oyster Grey **874**



Granite Rock **179**

CADANGAN SISTEM SALUTAN

Recommended Coating System



CAT ASAS <i>Sealer</i>	5200 Interior Sealer / 5300 Basecoat Sealer / 5400 Wall Sealer / Acrylic 5170 Wall Sealer / Hi-Bond Wall Sealer	1 lapisan/coat
CAT <i>Topcoat</i>	MatexPro	2 lapisan/coats

DATA PENGGUNAAN

Application Data



TEMPOH KERING / *Drying Time:*

Kering Disentuh / *Touch Dry* : 15 minit/minutes

Kering Sempurna / *Hard Dry* : 1 jam/hour

Tempoh Lapisan Semua / *Recoating Time* : 2 jam/hours

(Bergantung kepada suhu dan kelembapan / *Dependent on temperature and humidity*)

Liputan Teori / *Theoretical Coverage* : 10-12 m² seliter
/per liter

(Bergantung pada keadaan asas / *Dependent on substrate condition*)

Cara Penggunaan / *Application Method:*

Cairkan dengan maksimum 10% air bagi lapisan pertama dan kedua.

Dilute the paint with 10% of water for 1st and 2nd coat.

PENYEDIAAN PERMUKAAN

Surface Preparation



Tanggalkan semua cat yang mengelupas atau baki berserbuk. Baiki permukaan yang tidak rata dengan Nippon Paint Multi-Purpose Joint Compound atau likatan yang sesuai. Ratakan kawasan likatan (putty/filler) dengan kertas pasir. Pastikan permukaan yang hendak dicat benar-benar bersih dan kering serta bebas daripada kotoran, minyak dan sebarang bahan-bahan pencemaran lain. Biarkan permukaan benar-benar bersih dan kering sebelum kerja mengecat dimulakan. Jangan mengecat jika kadar kelembapan dan kealkalian permukaan dinding masih tinggi.

Remove all loose, defective paint or powdery residues, loose chalk, dust, fungus, algae and foreign matter. Repair cracks, uneven surfaces with Nippon Paint Multi-Purpose Joint Compound or suitable fillers. Smoothen the putty/filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high.



**THE
COATINGS
EXPERT®**

NIPPON PAINT (M) SDN. BHD. (196701000578)

Lot I-17, Taman Perindustrian Subang Utama, Jalan SU 4,
40300 Shah Alam, Selangor Darul Ehsan, Malaysia.

☎ 1-800-88-2663 ✉ customercare@nipponpaint.com.my

🏠 www.nipponpaint.com.my 🌐 facebook.com/nipponpaintmalaysia